

All Sizes

IMP / 80

TIRE SIZE	PR	TT/TL	LOAD INDEX	SPEED SYMBOL	RIM		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS (W/LOAD)		INFLATING PRESSURE (psi)	LOAD CAPACITY PER TIRE (KG)					
					RECOM. (INCHES)	PERMITTED (INCHES)	Section Width Min-Max	OUTER DIAMETER (MM)	DYNAMIC RADIUS CIRCLE (MM)	STATIC LOADED RADIUS (MM)		Speed (KM/H)					
												10	15	20	25	30	40
10.0/75-15.3	10	TT	123	A8	9.00	-	264	760	2368	352	46 / 2.0	1745			1430	1300	
		TT	123	A8	9.00	-	264	760	2368	352	52 / 4.0	1910			1570	1425	
		TT	123	A8	9.00	-	264	760	2368	352	56 / 3.9	2075			1705	1550	
	12	TL	123	A8	9.00	-	264	760	2368	352	52 / 3.6	1905			1550	1410	
		TL	123	A8	9.00	-	264	760	2368	352	58 / 4.0	2110			1720	1565	
		TL	123	A8	9.00	-	264	760	2368	352	68 / 4.7	2295			1870	1700	
10.0/75-15.3RF	10	TL	123	A8	9.00	-	264	760	2368	352	46 / 3.2	1745			1430	1300	
		TL	123	A8	9.00	-	264	760	2368	352	52 / 3.6	1910			1570	1425	
		TL	123	A8	9.00	-	264	760	2368	352	56 / 3.8	2075			1705	1550	
	12	TL	126	A8	9.00	-	264	760	2368	352	52 / 3.6	1905			1550	1410	
		TL	126	A8	9.00	-	264	760	2368	352	58 / 4.0	2110			1720	1565	
		TL	126	A8	9.00	-	264	760	2368	352	68 / 4.7	2295			1870	1700	
10.5/65-16	10	TT	123	A8	W9	W8-W8L	274	775	2302	345	46 / 3.2	1745			1895	1720	
		TT	123	A8	W9	W8-W8L	274	775	2302	345	52 / 3.6	1930			2065	1335	
		TT	123	A8	W9	W8-W8L	274	775	2302	345	55 / 3.8	2075			1705	1550	
10.5/80-18	10	TT	131	A8	W9	W8-9	274	885	2768	412	40 / 2.8	2185			1780	1620	
		TT	131	A8	W9	W8-9	274	885	2768	412	46 / 3.2	2395			1950	1775	
		TT	131	A8	W9	W8-9	274	885	2768	412	54 / 3.7	2635			2145	1950	
	12	TT	137	A8	W9	W8-9	274	885	2768	412	46 / 3.2	2495			2050	1865	
		TT	137	A8	W9	W8-9	274	885	2768	412	52 / 3.6	2680			2200	2000	
		TT	137	A8	W9	W8-9	274	885	2768	412	60 / 4.1	3080			2530	2300	
	14	TT	142	A8	W9	W8-9	274	885	2768	412	50 / 3.6	2665			2185	1985	
		TT	142	A8	W9	W8-9	274	885	2768	412	58 / 4.0	2840			2330	2120	

TIRE SIZE	PR	TT/TL	LOAD INDEX	SPEED SYMBOL	RIM		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS (W/LOAD)		INFLATING PRESSURE (psi)	LOAD CAPACITY PER TIRE (KG)					
					RECOM. (INCHES)	PERMITTED (INCHES)	Section Width Min-Max	OUTER DIAMETER (MM)	DYNAMIC RADIUS CIRCLE (MM)	STATIC LOADED RADIUS (MM)		Speed (KM/H)					
												10	15	20	25	30	40
		TT	142	A8	W9	W8-9	274	885	2768	412	65 / 4.5	3550			2915	2650	
11.5/80-15.3	12	TT	135	A8	9.00	-	290	845	2600	382	46 / 3.2	2275			1895	1720	
		TT	135	A8	9.00	-	290	845	2600	382	52 / 3.6	2480			2065	1875	
		TT	135	A8	9.00	-	290	845	2600	382	60 / 4.1	2880			2400	2180	
		TL	135	A8	9.00	-	290	845	2600	382	46 / 3.2	2275			1895	1720	
		TL	135	A8	9.00	-	290	845	2600	382	60 / 4.1	2880			2400	2180	
		TL	135	A8	9.00	-	290	845	2600	382	52 / 3.6	2480			2065	1875	
		TL	135	A8	9.00	-	290	845	2600	382	46 / 3.2	2275			1895	1720	
11.5/80-15.3RF	12	TL	135	A8	9.00	-	290	845	2600	382	46 / 3.2	2275			1895	1720	
		TL	135	A8	9.00	-	290	845	2600	382	52 / 3.6	2480			2065	1875	
		TL	135	A8	9.00	-	290	845	2600	382	60 / 4.1	2880			2400	2180	
12.5/80-15.3	12	TL	139	A8	9.00	-	307	889	2650	390	40 / 2.8	2695			2215	2015	
		TL	139	A8	9.00	-	307	889	2650	390	46 / 3.2	2955			2430	2210	
		TL	139	A8	9.00	-	307	889	2650	390	54 / 3.7	3250			2670	2430	
	16	TL	144	A8	9.00	-	307	889	2650	390	54 / 3.7	3225			2650	2408	
		TL	144	A8	9.00	-	307	889	2650	390	60 / 4.1	3525			2895	2632	
		TL	144	A8	9.00	-	307	889	2650	390	71 / 4.9	3750			3080	2800	
		TL	139	A8	9.00	-	307	889	2650	390	40 / 2.8	2695			2215	2015	
12.5/80-15.3RF	12	TL	139	A8	9.00	-	307	889	2650	390	46 / 3.2	2955			2430	2210	
		TL	139	A8	9.00	-	307	889	2650	390	54 / 3.7	3250			2670	2430	
		TT	142	A8	W9	11	308	965	2915	431	40 / 2.8	2910			2185	1985	
12.5/80-18	12	TT	142	A8	W9	11	308	965	2915	431	46 / 3.2	3125			2330	2120	
		TT	142	A8	W9	11	308	965	2915	431	54 / 3.7	3550			2915	2650	
		TT	146	A8	W9	11	308	965	2915	431	50 / 3.6	3195			2625	2700	
	14	TT	146	A8	W9	11	308	965	2915	431	58 / 4.0	3340			3100	2490	
		TT	146	A8	W9	11	308	965	2915	431	65 / 4.5	4020			3300	3000	
		TT	138	A8	11	-	336	890	2828	420	40 / 2.8	2580			2100	1910	

TIRE SIZE	PR	TT/TL	LOAD INDEX	SPEED SYMBOL	RIM		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS (W/LOAD)		INFLATING PRESSURE (psi)	LOAD CAPACITY PER TIRE (KG)					
					RECOM. (INCHES)	PERMITTED (INCHES)	Section Width Min-Max	OUTER DIAMETER (MM)	DYNAMIC RADIUS CIRCLE (MM)	STATIC LOADED RADIUS (MM)		Speed (KM/H)					
												10	15	20	25	30	40
		TT	138	A8	11	-	336	890	2828	420	46 / 3.2	2800			2285	2075	
		TT	138	A8	11	-	336	890	2828	420	52 / 3.6	3185			2595	2360	
		14	TT	141	A8	11	-	336	890	2828	420	50 / 3.6	2945			2435	2215
			TT	141	A8	11	-	336	890	2828	420	58 / 4.0	3150			2605	2370
			TT	141	A8	11	-	336	890	2828	420	63 / 4.3	3425			2830	2575
15.0/55-17	14	TL	137	A8	13.00	13	391	850	2467	370	40 / 2.8	2490			2050	1860	
		TL	137	A8	13.00	13	391	850	2467	370	46 / 3.2	2710			2225	2025	
		TL	137	A8	13.00	13	391	850	2467	370	52 / 3.6	3080			2530	2300	
19.0/45-17	12	TL	141	A8	16.00	-	491	866	2615	388	40 / 2.8	3070			2520	2290	
		TL	141	A8	16.00	-	491	866	2615	388	46 / 3.2	3280			2690	2445	
		TL	141	A8	16.00	-	491	866	2615	388	48 / 3.3	3450			2830	2575	
340/55-16	12	TL	140	A8	11.00	-	343	780	2316	347							
400/60-15.5	14	TL	145	A8	AG13.00	-	404	874	2661	390	40 / 2.8	3145			2580	2350	
		TL	145	A8	AG13.00	-	404	874	2661	390	46 / 3.2	3380			2775	2520	
		TL	145	A8	AG13.00	-	404	874	2661	390	52 / 3.6	3885			3190	2900	
500/50-17	10	TL	143	A8	16.00	-	503	932	2846	420	23 / 1.6	3005			2550	2315	
		TL	143	A8	16.00	-	503	932	2846	420	26 / 1.8	3220			2730	2480	
		TL	143	A8	16.00	-	503	932	2846	420	29 / 2.0	3540			3000	2725	
	14	TL	149	A8	16.00	-	503	932	2846	420	35 / 2.4	3595			2930	2665	
		TL	149	A8	16.00	-	503	932	2846	420	38 / 2.6	3905			3180	2890	
		TL	149	A8	16.00	-	503	932	2846	420	41 / 2.8	4388			3575	3250	